





# PLESK - Node.js Einstellungen




Websites & Domains >

## Node.js on [dess-klosterneuburg.agrarforschung.at](http://dess-klosterneuburg.agrarforschung.at)

 Restart App  NPM install  Run script  Disable Node.js

Node.js Version	<a href="#">12.4.0</a>
Document Root	<a href="#">/dess-klosterneuburg.agrarforschung.at</a>
Application Mode	<a href="#">production</a>
Application URL	<a href="http://dess-klosterneuburg.agrarforschung.at">http://dess-klosterneuburg.agrarforschung.at</a>
Application Root	<a href="#">/dess-klosterneuburg.agrarforschung.at</a> <a href="#">[open]</a>
Application Startup File	<a href="#">index.js</a> <a href="#">[edit]</a>
Custom environment variables	<div>- NODE_ENV: production - PROXY: true <a href="#">[specify]</a></div>

## Custom Environment Variable:

Custom environment variables	<input type="text" value="NODE_ENV"/>	<input type="text" value="production"/>	 Remove
	<input type="text" value="PROXY"/>	<input type="text" value="true"/>	 Remove
 Add variable			
<input type="button" value="OK"/>		<input type="button" value="Cancel"/>	

Version #3

★ Erstellt: 28 April 2021 13:31:20 von roland.neissl

🔧 Zuletzt aktualisiert: 11 Oktober 2021 13:58:15 von roland.neissl